

F210 Payment Android POS



SPECIFICATIONS



F210	
Operating System	Android 12
Processor	Quad-Core 4*A53@1.4GHz
Memory	RAM: 1GB + ROM: 8GB
Communications	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4&5GHz (optional: 2.4GHz), Bluetooth 4.2/BLE
Location	GPS, BeiDou/GLONASS
Display	5.0 inch, IPS LCD, 1280*720 Pixel, Multi-touch
Cameras	Rear: 8MP AF with Flash LED Front: 2MP FF Support 1D/2D barcode
Printer	Thermal printer, Paper size: 58mm*40mm
Battery	3.8V/5000mAh
Magnetic Card Reader	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
NFC	13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type A&B, Felica, Mifare card
Card Slot	Micro SIM*2 + PSAM*1 + TF Card*1 (TF, Max support 256GB)
Peripheral Port	Type C*1 (USB2.0, OTG)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A
Physical	197mm (L)*82.1mm (W)*52.5mm (H)
Weight	410g

F210 ^[B]	
Operating System	Android 12
Processor	Quad-Core 4*A53@1.4GHz
Memory	RAM: 1GB + ROM: 8GB
Communications	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4GHz (optional: 5GHz), Bluetooth 4.2/BLE
Location	GPS, BeiDou/GLONASS
Display	5.0 inch, IPS LCD, 854*480 Pixel, Multi-touch
Camera	Rear: 2MP AF with Flash LED Support 1D/2D barcode
Printer	Thermal printer, Paper size: 58mm*40mm
Battery	3.8V/5000mAh
Magnetic Card Reader	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
NFC	13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type A&B, Felica, Mifare card
Card Slot	Micro SIM*2 + PSAM*1 + TF Card*1 (TF, Max support 256GB)
Peripheral Port	Type C*1 (USB2.0, OTG)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A
Physical	197mm (L)*82.1mm (W)*52.5mm (H)
Weight	410g

F210 ^[U5]	
Operating System	Android 12
Processor	Quad-Core 4*A53@1.4GHz
Memory	RAM: 1GB + ROM: 8GB
Communications	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4GHz (optional: 5GHz), Bluetooth 4.2/BLE
Location	GPS, BeiDou/GLONASS
Display	5.0 inch, IPS LCD, 854*480 Pixel, Multi-touch
Camera	Rear: 2MP AF with Flash LED Support 1D/2D barcode
Printer	Thermal printer, Paper size: 58mm*40mm
Battery	3.7V/5200mAh
Magnetic Card Reader	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
NFC	13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type A&B, Felica, Mifare card
Card Slot	Micro SIM*2 + PSAM*1 + TF Card*1 (TF, Max support 256GB)
Peripheral Port	Type C*1 (USB2.0, OTG)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A
Physical	197mm (L)*82.1mm (W)*52.5mm (H)
Weight	410g

Environment	Operating Temperature: -10°C ~ 50°C (14°F~122°F), Storage Temperature: -20°C ~ 70°C (-4°F~158°F) , Relative Humidity: 5%-96% (Non-Condensing)
Accessories	Adapter*1, USB Cable (only charging)*1, Manual*1
Certifications	PCI, EMV L1&L2, EMV Contactless L1, Amex, PayWave, Paypass, Discover, JCB, Pure, qUICS, MIR, NTRA-VOC, WEEE, CE, FCC, CB, CMC, GSMA, TQM, ANRT, CCC, SRRC, Nal Certificate, UPTS3.0, PBOC3.0 L1&CL1, PBOC3.0 CL2, DGM, UN38.3, MSDS

www.rsa.ir

Unit 10, No.58, Ebrahimi St., Teymoori Blvd., Tehran, Iran, 1458995004

Tel: +98 21 66016033 Fax: +98 21 66013776

Email: info@rsa.ir Website: www.rsa.ir